

SPECIFICATIONS PVM® 328

**Element Type:**

Neodymium Dynamic Microphone

Sensitivity:

-53 dBV/pa (2.2 mv/pa)

Polar Pattern:

Super Cardioid

Max SPL:

134 dB (THD 1% 1kHz)

Rated Output Impedance:

500 Ohms

Connector:

3-pin XLR

Frequency Response:

20 Hz – 12,500 Hz

Polarity:

Positive pressure on the diaphragm produces positive voltage at pin 2 relative to pin 3

Dimensions:

1.695" (43.053 mm) maximum diameter (without stand adapter), 5.025" (127.635 mm) long

Packaging:

Packaged in a molded microphone carrying case. Comes equipped with a body-mounted stand adapter, 20' (6 meter) right angle microphone cable and rim clip.

Also available in kit form, the DMS-5 drum kit, which includes 1 – PVM 321, 1 – PVM 325, and 3 – PVM 328 microphones rim clips and cables.

Net Weight:

10.93 ounces (310 grams)

Features

- Wide frequency response
- High gain before feedback
- Super Cardioid pattern
- Designed for use with tom drum or other wide dynamic range instruments
- Superb low frequency response
- Portable microphone case
- Mic cable with a 90° female XLR connector
- Rim mount clip

Description:

The PVM® 328 is a dynamic, super cardioid microphone specifically designed for tom drum or recording project applications. Its response, however, permits unlimited use for



LISTEN TO THIS™

SPECIFICATIONS PVM® 328

any tom drum, percussion instrument or any other mid frequency applications. With high sensitivity and excellent gain before feedback, the PVM 328 microphone also has an extremely wide linear dynamic range and high SPL endurance.

Peavey engineering applied extensive research and development time to develop this mic for groups looking for application-specific microphones. The PVM 328, in combination with the PVM 321 (drum mic) and PVM 325 (snare mic), gives the performer a complete set for any drum micing application.

Architectural & Engineering Specifications

The microphone shall be a moving coil dynamic with a frequency response of 20 Hz to 12.5 kHz. The microphone shall have a super cardioid polar characteristic typically 15 dB down from the front response. The microphone shall have an output power level of -53 dB where 0 dB = 1 milliwatt per pascal and a nominal impedance of 500 Ohms. The microphone shall have a black finish that can withstand the toughest conditions. The microphone shall have a 3-pin XLR connector or

equivalent audio type. The microphone shall have an overall dimension of 5.03" x 1.69". The microphone shall be a PVM 328 or equivalent.

3 + 2 Year Limited Warranty

NOTE: For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P.O. Box 2898, Meridian, Mississippi 39301-2898.

Features and specifications subject to change without notice.

Peavey Electronics Corporation • 711 A Street • Meridian • MS • 39301 (601) 483-5365 • FAX (601) 486-1278 • www.peavey.com
©2001 Printed in the U.S.A. 3/01



LISTEN TO THIS™