

## SPECIFICATIONS

## Headliner™ 210 Bass Cabinet



**Frequency response, 1 meter on-axis, swept-sine in anechoic environment:**

54 Hz to 6 kHz

**Power handling:**

200W RMS  
400W program  
800W peak

**Transducer complement:**

Two 10" heavy-duty ferrite magnet woofers

**Impedance (Z):**

8 ohms

**Input connections:**

One 4-pin twist-lock connector, in parallel with two 1/4" phone jacks.

**Enclosure:**

Internally braced cabinet in black carpet, with a full coverage 16 ga. perforated metal grille.

**Transport provisions:**

Steel handles, one on each side

**Dimensions (H x W x D):**

16.63" x 23.38" x 18.38"  
422 mm x 594 mm x 467 mm

**Net weight:**

52 Lbs. (23.6 kg)

**Features:**

- 2 Custom designed ceramic magnet 10" woofers
- 400W program power handling
- 8 ohm impedance
- Internal cabinet bracing
- Durable black carpet covering
- 16 Ga. Perforated metal grille
- Two 1/4" input jacks, and one 4-pin twist-lock connector
- Steel corners for road durability

**Description:**

The new Headliner™ series has been re-designed from the ground up for the serious bass player on a budget. Voiced for punchy bass with lots of harmonic tone, the versatility and performance of the Headliner™ 210 encourages use with any fine bass amp head.

The Headliner™ 210 is constructed using internal bracing, and is covered with road-worthy black carpet. Steel corners protect the cabinet from the rigors of the road. The cabinet includes a black powdercoat finished 16 gauge perforated metal grille. The two 10" ferrite magnet woofers are designed with a rich bass tone in mind. The sealed cabinet insures

tight bass notes, with every note rendered precisely. Inputs include two 1/4" input phone jacks, and one 4-pin twist-lock connector for maximum flexibility.

With a nominal impedance of 8 ohms, and a power handling of 400 watts program and 800 watts peak, the Headliner™ 210 can be used in conjunction with any reasonably sized bass amp head. With the 8 ohm impedance, the Headliner™ 210 can be easily stacked on top of a Headliner™ 410 cabinet, resulting in a 4 ohm total load.

Be sure to check the amplifier specifications to verify the minimum impedance rating of the amp used to power the stacked pair of speakers.

**3 + 2 YEAR LIMITED WARRANTY**

**NOTE:** For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P.O. Box 2898, Meridian, Mississippi 39301-2898, or on our website at <http://www.peavey.com/support/warrantyregistration/warrantytext.cfm>.



Logo referenced in Directive 2002/96/EC Annex IV (OJ(L)37/38,13.02.03 and defined in EN 50419: 2005  
The bar is the symbol for marking of new waste and is applied only to equipment manufactured after 13 August 2005

Features and specifications subject to change without notice.

Peavey Electronics Corporation • 5022  
Hartley Peavey Drive • Meridian, MS • 39305  
(601) 483-5365 • FAX (601) 486-1278  
[www.peavey.com](http://www.peavey.com) ©2010 EX000078

